

Safety Data Sheet



Superior Solutions

Zep, Inc.
1310 Seaboard Industrial Blvd.
Atlanta, GA 30318
1-877-I-BUY-ZEP (428-9937)
www.zep.com

Section 1. Chemical Product and Company Identification

Product name STAINLESS STEEL POLISH
Product use Aerosol Cleaner and Polish
Product code 0143
Date of issue 09/23/13 **Supersedes** 08/28/12

Emergency Telephone Numbers

For MSDS Information:

Compliance Services 1-877-I-BUY-ZEP (428-9937)

For Medical Emergency

(877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded
In the District of Columbia (202) 483-7616

Prepared By

Compliance Services
1259 Seaboard Industrial Blvd.
Atlanta, GA 30318


Section 2. Hazards Identification

Emergency overview

*Hazard Determination System (HDS): Health, Flammability, Reactivity

DANGER !

FLAMMABLE. CONTENTS UNDER PRESSURE. CAUSES EYE IRRITATION. HARMFUL OR FATAL IF SWALLOWED.



NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Dermal contact. Eye contact. Inhalation.

Eyes

Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

Skin

May cause skin irritation. Skin inflammation is characterized by itching, scaling, or reddening. May cause allergic reactions in certain individuals.

Inhalation

Avoid direct inhalation of spray. Inhalation of high concentrations of dust may cause respiratory irritation. Inhalation of spray mists or vapors may cause central nervous system depression characterized by headache, dizziness, nausea, and/or stupor.

Ingestion

Harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage. Call physician immediately.

Chronic effects

Contains material which may cause damage to the following organs: blood, kidneys, lungs, liver, spleen, skin, upper respiratory tract, central nervous system (CNS), ears, eyes, eye, lens or cornea. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation.

Carcinogenicity Classification

Additional information: See toxicological information (Section 11)

Section 3. Composition/Information on Ingredients

Name	CAS number	%
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	60-70
Distillates (petroleum), hydrotreated light	64742-47-8	15-25
d-Limonene; (R)-p-mentha-1,8-diene	5989-27-5	1-5
Carbon dioxide	124-38-9	1-5
Isopropyl alcohol	67-63-0	1-5

Section 4. First Aid Measures

Eye Contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.
Skin Contact	Wash affected area with soap or mild detergent and water. Remove contaminated clothing and shoes. Get medical attention if irritation develops.
Inhalation	Move exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Ingestion	Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



Flash Point	Not available.
Flammable Limits	Not available.
Flammability	FLAMMABLE. (CSMA Method)
Fire hazard	CONTENTS UNDER PRESSURE. Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.
Fire-Fighting Procedures	Use an extinguishing agent suitable for the surrounding fire. Cool closed containers exposed to fire with water. Fire-fighters should wear appropriate protective equipment.

Section 6. Accidental Release Measures

Spill Clean up	Large spills are unlikely due to packaging.
-----------------------	---

Section 7. Handling and Storage

Handling	Put on appropriate personal protective equipment (see Section 8). Store and use away from heat, sparks, open flame or any other ignition source. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Observe label precautions. Wash contaminated clothing before reusing. Wash thoroughly after handling.
Storage	CONTENTS UNDER PRESSURE. Eliminate all ignition sources. Do not puncture, incinerate or store the container at temperatures above 49°C (120°F) or in direct sunlight. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection

Ingredient	Exposure limits
Distillates (petroleum), hydrotreated heavy naphthenic	ACGIH TLV (United States, 3/2012). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 1/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist OSHA PEL (United States, 6/2010). TWA: 5 mg/m ³ 8 hours.
Distillates (petroleum), hydrotreated light	ACGIH TLV (United States, 3/2012). Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours.
Carbon dioxide	ACGIH TLV (United States, 3/2012). Oxygen Depletion [Asphyxiant]. TWA: 5000 ppm 8 hours. TWA: 9000 mg/m ³ 8 hours. STEL: 30000 ppm 15 minutes. STEL: 54000 mg/m ³ 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 10000 ppm 8 hours. TWA: 18000 mg/m ³ 8 hours. STEL: 30000 ppm 15 minutes. STEL: 54000 mg/m ³ 15 minutes. NIOSH REL (United States, 1/2013). TWA: 5000 ppm 10 hours. TWA: 9000 mg/m ³ 10 hours. STEL: 30000 ppm 15 minutes. STEL: 54000 mg/m ³ 15 minutes. OSHA PEL (United States, 6/2010). TWA: 5000 ppm 8 hours. TWA: 9000 mg/m ³ 8 hours.
Isopropyl alcohol	ACGIH TLV (United States, 3/2012). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 400 ppm 8 hours.

TWA: 980 mg/m³ 8 hours.
 STEL: 500 ppm 15 minutes.
 STEL: 1225 mg/m³ 15 minutes.
NIOSH REL (United States, 1/2013).
 TWA: 400 ppm 10 hours.
 TWA: 980 mg/m³ 10 hours.
 STEL: 500 ppm 15 minutes.
 STEL: 1225 mg/m³ 15 minutes.
OSHA PEL (United States, 6/2010).
 TWA: 400 ppm 8 hours.
 TWA: 980 mg/m³ 8 hours.

Personal Protective Equipment (PPE)

Eyes Safety glasses.

Body Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves.



Respiratory Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate.

Section 9. Physical and Chemical Properties

Physical State Liquid. [Aerosol.]

pH Not applicable

Boiling Point 82.22°C (180°F)

Specific Gravity 0.856

Solubility Insoluble in the following materials: cold water and hot water.

Color Amber.

Odor Citrus

Vapor Pressure Not determined.

Vapor Density Not determined.

Evaporation Rate Not determined.

VOC (Consumer) 14.7 % (w/w) 1.05 lbs/gal (125.6 g/l)

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Incompatibility Avoid contact with strong oxidizers, excessive heat, sparks or open flame.

Hazardous Polymerization Under normal conditions of storage and use, hazardous polymerization will not occur.

Hazardous Decomposition Products carbon oxides (CO, CO₂)

Section 11. Toxicological Information

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), hydrotreated light	LC50 Inhalation	Rat	>6.8 mg/l	4 hours
	Vapor			
	LD50 Dermal	Rabbit	2000 to 4000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
d-Limonene; (R)-p-mentha-1,8-diene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	4400 mg/kg	-
Isopropyl alcohol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-

Section 12. Ecological Information

Environmental Effects

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated light	Acute LC50 2200 µg/l Fresh water	Fish - Lepomis macrochirus	4 days
d-Limonene; (R)-p-mentha-1,8-diene	Acute EC50 421 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 688 µg/l Fresh water	Fish - Pimephales promelas	96 hours
Isopropyl alcohol	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1400000 µg/l	Fish - Gambusia affinis	96 hours

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Code: D001

Classification: Ignitable hazardous waste.

Origin: RCRA waste.

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not available.	Consumer commodity	ORM-D	-	
IMDG Class	UN1950	Aerosols, flammable, or Limited quantity	2.1	-	

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

Product name

No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

State Regulations**California Prop 65**

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer.

WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.