

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION					
NFPA Rating: Health-1; Flammability-1; Reactivity-0; Special- -			HMIS Rating: Health-1; Flammability-1; Reactivity-0; Personal Protection-B		
Manufactured For: Hillyard Industries, Inc. Address: 302 N. 4 th Street Address: St. Joseph, MO 64501			DOT Hazard Classification: ORM-D Identity (trade name as used on label): SPRAY CLEANER Part# HIL0102754		
Phone: (816)-233-1321 ext. 8285 or http://www.hillyard.com			MSDS Number: A00170 Revision- 14		
EMERGENCY RESPONSE NUMBER: Chemtrec 1-800-424-9300			Date Prepared: 09/27/07 Prepared By: RC/IB		
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA					
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)
ISOBUTANE / PROPANE BLEND		75-28-5	No	NE	NE
		74-98-6	No	1000	1000
ETHYLENE GLYCOL MONOBUTYL ETHER (*GLYCOL ETHER)		111-76-2	Yes*	50	20
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS					
Boiling Point: N/A			Specific Gravity (H2O=1): Concentrate Only = 1.0		
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.55			Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A		
Vapor Density (Air = 1): N/E			Evaporation Rate (= 1): N/E		
Solubility in Water: Soluble			Water Reactive: No		
Appearance and Odor: White foam, slight ammonical with mint fragrance.					
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA					
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) less than 18 inch flame projection NOT CATEGORIZED AS FLAMMABLE		Auto Ignition Temperature N/E		Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E	
FLASH POINT AND METHOD USED (non-aerosols): N/A			EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.		
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.					
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.					
SECTION 4 - REACTIVITY HAZARD DATA					
STABILITY ☒ STABLE ☐ UNSTABLE			HAZARDOUS POLYMERIZATION ☐ WILL ☒ WILL NOT OCCUR		
Incompatibility (Mat. to avoid): Copper, alkali metals.			Conditions to Avoid: Open flame, welding arcs, heat.		
Hazardous Decomposition Products: CO, CO2 and trace oxides of phosphate and nitrogen.					
SECTION 5 - HEALTH HAZARD DATA					
PRIMARY ROUTES OF ENTRY: ☒ INHALATION ☐ INGESTION ☒ SKIN ABSORPTION ☒ EYE ☐ NOT HAZARDOUS					
ACUTE EFFECTS					
Inhalation: Excessive inhalation of vapors can be harmful & may cause headache, dizziness, asphyxia, anesthetic effects & possible unconsciousness.					
Eye Contact: Irritation.			Skin Contact: May cause irritation.		
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.					
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause damage to nasal & respiratory passages, throat & esophagus. Lab animals have experienced anemia, liver, kidney, lung, blood damage to ethylene glycol monobutyl ether.					
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.					
EMERGENCY FIRST AID PROCEDURES					
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.					
Skin Contact: Wash with soap and water. If irritated, seek medical attention.					
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.					
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.					
SECTION 6 - CONTROL AND PROTECTIVE MEASURES					
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH in positive pressure mode for organic vapor & mist.					
Protective Gloves: Latex gloves recommended.			Eye Protection: Safety glasses recommended.		
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.					
Other Protective Clothing & Equipment: None					
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.					
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE					
Steps To Be Taken If Material Is Spilled Or Released: Dilute with water, absorb with suitable medium or neutralize with dilute acid & flush to sewer with water.					
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.					
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 120°F.					
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.					

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only